

Running XML Import on UNIX at the command line

Set environment variables before running XML Import outside Central

Prior to the 5.6 release of Adobe Central Output Server (Central) for UNIX, there was an executable called “XMLImport” and a script called “xmlimport” (note the case difference). Effective with the 5.6 release of the product, the logic from the xmlimport script was moved into Central. As a result of the change, the name of the xmlimport executable was changed to “xmlimport” (all lower case) and the script which had that name was abolished.

The changes in the 5.6 release of Central require that if you want to run XML Import outside of Central (that is, at the command line), you must set the NLSPATH and the appropriate library path. Without the proper settings, you will get the following error when you try to execute XML Import at the command line:

```
/usr/local/adobe/central/bin/xmlimport: can't find resource file jftools.cat!  
Exiting...
```

Of course, if you have installed Central to other than the default location, your error message will reflect your installation path.

Before running XML Import outside Central, set the environment variables documented on page 11 of the XML Import Agent Reference. You can find this guide in the Documentation folder of your installation of Central.

Product

Adobe Central Output Server, Version 5.6

Platform(s)

HP-UX 11.0
HP-UX 11i
IBM AIX 5.2, 5.3
LINUX Red Hat 3.0, 4.0
LINUX SuSE 8, 9
Sun Solaris 9, 10

Published

August 22, 2006