

# ADOBE® PDF TEST TOOLKIT

## APTT User Guide

### Automating PDF Testing for the Enterprise

Installation

Testing User Guide

FAQ and Examples



Acrobat® Family of Products  
Modification date: 8/6/12



## Adobe® PDF Test Toolkit User Guide.

If this guide is distributed with software that includes an end user agreement, this guide, as well as the software described in it, is furnished under license and may be used or copied only in accordance with the terms of such license. Except as permitted by any such license, no part of this guide may be reproduced, stored in a retrieval system, or transmitted, in any form or by any means, electronic, mechanical, recording, or otherwise, without the prior written permission of Adobe Systems Incorporated. Please note that the content in this guide is protected under copyright law even if it is not distributed with software that includes an end user license agreement.

The content of this guide is furnished for informational use only, is subject to change without notice, and should not be construed as a commitment by Adobe Systems Incorporated. Adobe Systems Incorporated assumes no responsibility or liability for any errors or inaccuracies that may appear in the informational content contained in this guide.

Please remember that existing artwork or images that you may want to include in your project may be protected under copyright law. The unauthorized incorporation of such material into your new work could be a violation of the rights of the copyright owner. Please be sure to obtain any permission required from the copyright owner.

Any references to company names in sample templates are for demonstration purposes only and are not intended to refer to any actual organization.

Adobe, Acrobat®, Reader®, and the Adobe logo are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Windows®, Windows NT®, and Windows XP® are registered trademarks of Microsoft® Corporation registered in the United States and/or other countries. Mac® and Macintosh® are registered trademarks of Apple Computer®, Inc. in the United States and other countries. All other trademarks are the property of their respective owners.

Adobe Systems Incorporated, 345 Park Avenue, San Jose, California 95110, USA. Notice to U.S. Government End Users. The Software and Documentation are "Commercial Items," as that term is defined at 48 C.F.R. §2.101, consisting of "Commercial Computer Software" and "Commercial Computer Software Documentation," as such terms are used in 48 C.F.R. §12.212 or 48 C.F.R. §227.7202, as applicable. Consistent with 48 C.F.R. §12.212 or 48 C.F.R. §§227.7202-1 through 227.7202-4, as applicable, the Commercial Computer Software and Commercial Computer Software Documentation are being licensed to U.S. Government end users (a) only as Commercial Items and (b) with only those rights as are granted to all other end users pursuant to the terms and conditions herein. Unpublished-rights reserved under the copyright laws of the United States. Adobe Systems Incorporated, 345 Park Avenue, San Jose, CA 95110-2704, USA. For U.S. Government End Users, Adobe agrees to comply with all applicable equal opportunity laws including, if appropriate, the provisions of Executive Order 11246, as amended, Section 402 of the Vietnam Era Veterans Readjustment Assistance Act of 1974 (38 USC 4212), and Section 503 of the Rehabilitation Act of 1973, as amended, and the regulations at 41 CFR Parts 60-1 through 60-60, 60-250, and 60-741. The affirmative action clause and regulations contained in the preceding sentence shall be incorporated by reference.

---

# Contents

---

<b>1</b>	<b>Installation and Configuration .....</b>	<b>4</b>
1.1	What is the Adobe PDF Test Toolkit? .....	4
1.2	System requirements .....	4
1.3	Installation .....	5
1.3.1	Install the PDF viewing client.....	5
1.3.2	Install the Adobe PDF Test Toolkit .....	5
1.3.3	Optional: Install components to support Flex testing .....	6
1.3.3.1	Install Flex Builder.....	6
1.3.3.2	Install the Flex plug-in for Quick Test Pro .....	6
1.3.4	Verify the server software .....	8
1.3.5	Install Quick Test Professional.....	8
1.3.6	Windows 7 and Vista and QTP .....	10
1.4	Uninstalling the Adobe PDF Test Toolkit.....	11
1.5	Registry changes .....	11
<b>2</b>	<b>Guidelines for Creating Tests .....</b>	<b>18</b>
2.1	Guidelines for successful tests .....	18
2.2	Supported form elements .....	18
2.3	Creating a new test script.....	19
2.3.1	Server testing .....	19
2.3.2	Acrobat and Adobe Reader testing .....	20
2.3.3	Browser viewer testing .....	21
2.4	Testing events .....	21
2.5	Checkpoint properties.....	24
2.6	Learning objects in the object repository .....	25
2.7	Miscellaneous FAQs and operational details .....	26
2.8	Errors.....	27
<b>3</b>	<b>Example QTP Tests .....</b>	<b>28</b>
3.1	XML form in a browser.....	28
3.2	Accessing unexposed properties.....	29
<b>4</b>	<b>Index.....</b>	<b>30</b>

# 1

## Installation and Configuration

### 1.1 What is the Adobe PDF Test Toolkit?

The Adobe PDF Test Toolkit (APTT) is a Windows-based set of tools for the Acrobat family of products version 10.1.2 and later. It is designed to automate PDF forms workflow testing, including the following:

- Reader and Acrobat running both stand-alone and within a browser.
- LiveCycle ES, ADEP servers, and SAP.
- XML dynamic forms (XFA 3.0 for LiveCycle Designer; XFA 2.9 when workflows include the LC ES or ADEP server).
- Acroforms.
- Documents that have been “reader enabled” so that Adobe Reader users can perform actions that would otherwise be prohibited.

This early release is designed for integration with HP Quick Test Professional (QTP). While this product is “beta”, we believe it is stable enough to use to test production systems that utilize Adobe Reader and PDF Forms. Your interest, feedback, and comments will determine future development of the toolkit.”

**Note:** QTP is a functional user interface test automation tool from Hewlett Packard that enables user interface-based testing of software applications in complex workflows.

### 1.2 System requirements

In addition to the software and hardware requirements listed below, the person installing the APTT plugins on the client must have permissions to modify files and registry entries.

- All the system requirements defined by Acrobat or Adobe Reader 10.1.2.
- While APTT is only provided in English, it may be run in all multilingual and localized environments.

**Table 1 Software and hardware requirements**

Category	Requirement	Notes
<b>Client software</b>		
	Acrobat or Adobe Reader 10.1.2	Uninstall previous versions.
	Flex Builder 4.0	Optional: Only needed if testing against LiveCycle/ADEP UI which uses Flex. 4.0
	Flex QTP Plugin	Included with Flex Builder
	HP Quick Test Pro 9.5 with updates or version 10 or 11	
<b>Server software</b>		When testing includes LiveCycle ES or ADEP workflows

**Table 1 Software and hardware requirements**

Category	Requirement	Notes
	LiveCycle Server 8.2 or later, including ADEP 10.0 and later	
<b>Operating system</b>		
	Windows XP SP3	Requires IE 6 or later
	Windows Vista sp1	Requires IE 7 or later
	Windows 7	Requires IE 8 or later
<b>Browser</b>		
	IE 6, 7, or 8	For Windows XP
	IE 7	For Windows Vista
	IE 8 or 9	For Windows 7
<b>Hardware</b>	None	APTT supports the requirements specified by the Acrobat family of products and HP Quick Test Pro.

## 1.3 Installation

Environment configuration involves the following:

- [Install the PDF viewing client](#)
- [Install the Adobe PDF Test Toolkit](#)
- [Optional: Install components to support Flex testing](#)

**Tip:** When testing scenarios involve testing Flex-based user interface components, install the requisite version of Flex Builder and the related plugins. If LC ES or ADEP components are not tested, skip those steps.

- [Verify the server software](#)
- [Install Quick Test Professional](#)
- [Windows 7 and Vista and QTP](#)

### 1.3.1 Install the PDF viewing client

Install the appropriate PDF viewing software:

1. Uninstall any versions of Acrobat or Adobe Reader older than 10.1.2.
2. Install any 10.1.2 or later Adobe Reader or Acrobat product. Only 10.1.2 and later is supported and the directories, registry entries, and so on must exist prior to installing APTT.

### 1.3.2 Install the Adobe PDF Test Toolkit

Before installing APTT, make sure you have the requisite product versions installed and that all of the other system requirements are met.

To install APTT components:

1. Go to <https://prerelease.adobe.com/>, and log in.
2. Navigate to the PDF Test Toolkit area.
3. Download PDFTestToolkit\_<version>.zip.
4. Extract the file to any location.
5. Go to the Toolkit's plugins directory <Toolkit install location>\plugins\.
6. Copy the two plugins the install registration file to your PDF client's plugin directory: <PDF viewer install location>\Adobe\<product name><version>\<product>\plug\_ins\
  - AcroQTP.exe
  - Automation.api
  - regPDFTestToolkit.bat
  - pi\_brokers\AcroQTPBroker.exe
7. Double click the regPDFTestToolkit.bat file to register the plugins.
8. Press **Enter** when the command prompt verifies successful installation.

### 1.3.3 Optional: Install components to support Flex testing

This section is only for users who need QTP recording on Flex content. If your testing involves the server's Flex-based web interface, install the Flex plugin for QTP as described below. Otherwise, skip to "Install Quick Test Professional" on page 8.

#### 1.3.3.1 Install Flex Builder

1. Verify you have installed Flex Builder 4.0 or later. If you don't have the requisite software, see <http://www.adobe.com/products/flex/>.
2. Install and configure Flex Builder according to the Flex Builder documentation.

**Tip:** You do not need the Flex Automated Testing plugin or any of its configuration steps to use the Adobe PDF Testing Toolkit.


#### 1.3.3.2 Install the Flex plug-in for Quick Test Pro

install the Adobe Flex 3 Plug-in for HP Quick Test Pro. This plugin enables testing of LC or ADEP Flex-based user interface components.

There are two ways to get the plugin:

- **Flex Builder:** If you already have Flex Builder installed, you probably already have the installer in the Installer directory (Figure 1).
- **Web download:** Download the installer from [http://www.adobe.com/support/documentation/en/flex/3/releasenotes\\_flex3\\_fb.html#install\\_automated\\_testing](http://www.adobe.com/support/documentation/en/flex/3/releasenotes_flex3_fb.html#install_automated_testing).


Figure 1 Flex plugin directory



To install the Flex plugin:


1. Run the installer.
2. Go through all the screens and choose **Finish**.
3. Restart your machine.

Figure 2 Flex QTP plugin installer



**Note:** If a test requires this component and it is not installed, a warning may appear.

Figure 3 QTP: Missing Flex components warning



## 1.3.4 Verify the server software

APTT supports LiveCycle ES 8.2 and later, including LC ES 9.0-9.5 and ADEP 10.0 and later.

The Flex user interface is built using the Flex framework, and when compiled with automation libraries (or when the runtime loader loads it) that alone will make the QTP plugin work. The server does not do anything in particular to support automated testing, and no special configuration is required.

### Test URLs

Note that for testing, record and run properties must occur against a test URL for which the automation bits are turned on in the server's automation SWFs. These bits are on by default. For example, if server's main URL is:

```
http://<server name>:<server port>/<installation path>/Main.html
```

Then the URL to use for testing would be:

```
http://<server name>:<server port>/<installation path>/Main-auto.html
```

## 1.3.5 Install Quick Test Professional

If you don't already have Quick Test Professional 9.0 or later installed, install it now.


1. Run the installer.

**Note:** Running the installer automatically overwrites old plugin files. You do not need to delete them.

2. Install any required components the installer asks you to; for example, Microsoft Visual C++ Run-time Components.
3. Choose **Next** until you get to the Setup Type screen.
4. You can accept the basic installation; however, some components aren't needed. If you'd like to only install the components you need, do the following:
  1. Choose **Custom**.
  2. The following components are not required as part of the PDF Test Toolkit. Deselect them if you don't need them for other testing and would like a minimal install:
    - ActiveX Add-in
    - Visual Basic Add-in
    - Samples (under Quick Test Professional)
  3. Choose **Next** and continue the installation normally.




Figure 4 QTP: Custom installation




5. Choose **Finish** when done.
6. If an Additional Installation Requirements screen appears, choose any items or choose **Cancel**. APTT does not require any special configuration with respect to these items.

Figure 5 QTP: Additional installation components



7. Launch QTP.
8. If the Add In Manager appears, verify the needed add ins are checked:
  - **AcroQTP**: Required.
  - **Flex**: Required when testing a Flex-based web user interface.
  - **Web**: Required when testing a Flex-based web user interface.
9. Choose **OK**.

Figure 6 QTP: Add-In Manager



10. Install QTP updates. QTP should display a dialog on startup if you don't have the latest updates.

**Tip:** It may be useful to verify your system is set up correctly. To do so, load and run on of the APTT's test files included examples as described in ["XML form in a browser" on page 28](#).

### 1.3.6 Windows 7 and Vista and QTP

When testing on a machine running Vista, perform the following steps:

#### Configure IE

1. Open Internet Explorer.
2. Choose **Tools > Internet Options > Advanced**.
3. Check **Enable 3rd party extensions**.

#### Clear the User Account Control (UAC)

1. Log in as an administrator.
2. Choose **Control Panel > User Accounts > Change Security Settings**.
3. Uncheck **User Account Control (UAC) to help protect your computer**.
4. Choose **OK**.
5. Restart the machine.

## 1.4 Uninstalling the Adobe PDF Test Toolkit

To uninstall APTT components:

1. Go to the Toolkit's plugins directory <\$APTT install root>\plugins\.
2. Double click the unregPDFTestToolkit.bat file to unregister the plugins.
3. Delete all the APTT files.

## 1.5 Registry changes

The registry is automatically modified when the plugins are registered. The following is provided for informational purposes only during the beta releases of APTT.

Since there is no uninstaller, removal of the plugins leaves the entries shown in [Example 1.1](#).

### Example 1.1 Registry entries

Keys added: 39

```
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Packages\TEAPackage\Settings\AcroQTP
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode
HKEY_CLASSES_ROOT\AcroQTP.Proxy
HKEY_CLASSES_ROOT\AcroQTP.Proxy\CLSID
HKEY_CLASSES_ROOT\AcroQTP.Proxy\CurVer
HKEY_CLASSES_ROOT\AcroQTP.Proxy.1
HKEY_CLASSES_ROOT\AcroQTP.Proxy.1\CLSID
HKEY_CLASSES_ROOT\AppID\{78B32EBB-4F99-4ee7-A2DE-3655652719B2}
HKEY_CLASSES_ROOT\AppID\AcroQTP.exe
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}\LocalServer32
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}\ProgID
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}\Programmable
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}\TypeLib
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}\
VersionIndependentProgID
HKEY_CLASSES_ROOT\Interface\{82718C32-93CD-4ECC-BD6F-0F5AF70C4E89}
HKEY_CLASSES_ROOT\Interface\{82718C32-93CD-4ECC-BD6F-0F5AF70C4E89}\
ProxyStubClsid
HKEY_CLASSES_ROOT\Interface\{82718C32-93CD-4ECC-BD6F-0F5AF70C4E89}\
ProxyStubClsid32
HKEY_CLASSES_ROOT\Interface\{82718C32-93CD-4ECC-BD6F-0F5AF70C4E89}\TypeLib
HKEY_CLASSES_ROOT\Interface\{840E5481-71F5-4EC3-9C55-B916300405FE}
HKEY_CLASSES_ROOT\Interface\{840E5481-71F5-4EC3-9C55-B916300405FE}\
ProxyStubClsid
HKEY_CLASSES_ROOT\Interface\{840E5481-71F5-4EC3-9C55-B916300405FE}\
ProxyStubClsid32
HKEY_CLASSES_ROOT\Interface\{840E5481-71F5-4EC3-9C55-B916300405FE}\TypeLib
```

```
HKEY_CLASSES_ROOT\TypeLib\{2AABF103-0E9C-4F15-9F4E-3D344DFB9A30}
HKEY_CLASSES_ROOT\TypeLib\{2AABF103-0E9C-4F15-9F4E-3D344DFB9A30}\1.0
HKEY_CLASSES_ROOT\TypeLib\{2AABF103-0E9C-4F15-9F4E-3D344DFB9A30}\1.0\0
HKEY_CLASSES_ROOT\TypeLib\{2AABF103-0E9C-4F15-9F4E-3D344DFB9A30}\1.0\0\win32
HKEY_CLASSES_ROOT\TypeLib\{2AABF103-0E9C-4F15-9F4E-3D344DFB9A30}\1.0\FLAGS
HKEY_CLASSES_ROOT\TypeLib\{2AABF103-0E9C-4F15-9F4E-3D344DFB9A30}\1.0\HELPDIR
HKEY_CLASSES_ROOT\TypeLib\{C0FB90F3-F516-48B9-979A-4E60C7E69BF2}
HKEY_CLASSES_ROOT\TypeLib\{C0FB90F3-F516-48B9-979A-4E60C7E69BF2}\1.0
HKEY_CLASSES_ROOT\TypeLib\{C0FB90F3-F516-48B9-979A-4E60C7E69BF2}\1.0\0
HKEY_CLASSES_ROOT\TypeLib\{C0FB90F3-F516-48B9-979A-4E60C7E69BF2}\1.0\0\win32
HKEY_CLASSES_ROOT\TypeLib\{C0FB90F3-F516-48B9-979A-4E60C7E69BF2}\1.0\FLAGS
HKEY_CLASSES_ROOT\TypeLib\{C0FB90F3-F516-48B9-979A-4E60C7E69BF2}\1.0\HELPDIR
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Packages\TEAPackage\Settings\AcroQTP
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode
```

Values added: 55

```
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Packages\TEAPackage\Settings\AcroQTP "SnapshotMode"
Type: REG_DWORD
Data: 03, 00, 00, 00
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP "display name"
Type: REG_SZ
Data: AcroQTP
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "DefaultComplete"
Type: REG_DWORD
Data: 00, 00, 00, 00
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "DefaultMinimal"
Type: REG_DWORD
Data: 02, 00, 00, 00
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "DefaultNone"
Type: REG_DWORD
Data: 03, 00, 00, 00
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "DefaultPartial"
Type: REG_DWORD
Data: 01, 00, 00, 00
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "display name"
Type: REG_SZ
Data: Capture level
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "help string"
Type: REG_SZ
Data: Specifies which properties are captured for each object in a AcroQTP
application when it is captured for the Active Screen.
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "Internal Value"
Type: REG_SZ
Data: 3
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "type"
```

```
Type: REG_SZ
Data: selection 0\tComplete\n3\tPartial\n1\tMinimum\n2\tNone
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "Value path"
Type: REG_SZ
Data: Packages\TEAPackage\Settings\AcroQTP
HKEY_CLASSES_ROOT\AcroQTP.Proxy "(Default)"
Type: REG_SZ
Data: AcroQTP Proxy Class
HKEY_CLASSES_ROOT\AcroQTP.Proxy\CLSID "(Default)"
Type: REG_SZ
Data: {BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}
HKEY_CLASSES_ROOT\AcroQTP.Proxy\CurVer "(Default)"
Type: REG_SZ
Data: AcroQTP.Proxy.1
HKEY_CLASSES_ROOT\AcroQTP.Proxy.1 "(Default)"
Type: REG_SZ
Data: AcroQTP Proxy Class
HKEY_CLASSES_ROOT\AcroQTP.Proxy.1\CLSID "(Default)"
Type: REG_SZ
Data: {BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}
HKEY_CLASSES_ROOT\AppID\{78B32EBB-4F99-4ee7-A2DE-3655652719B2} "(Default)"
Type: REG_SZ
Data: AcroQTP.Proxy
HKEY_CLASSES_ROOT\AppID\AcroQTP.exe "AppID"
Type: REG_SZ
Data: {78B32EBB-4F99-4ee7-A2DE-3655652719B2}
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20} "(Default)"
Type: REG_SZ
Data: AcroQTP Proxy Class
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20} "AppID"
Type: REG_SZ
Data: {78B32EBB-4F99-4ee7-A2DE-3655652719B2}
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}\LocalServer32
"(Default)"
Type: REG_SZ
Data: "C:\Program Files\Adobe\Reader 10.0\Reader\plug_ins\Test_Tools\AcroQTP.
exe"
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}\ProgID
"(Default)"
Type: REG_SZ
Data: AcroQTP.Proxy.1
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}\TypeLib
"(Default)"
Type: REG_SZ
Data: {2AABF103-0E9C-4f15-9F4E-3D344DFB9A30}
HKEY_CLASSES_ROOT\CLSID\{BF95D3DB-AC03-46f1-97F1-C4B91F1A8F20}\
VersionIndependentProgID "(Default)"
Type: REG_SZ
Data: AcroQTP.Proxy
HKEY_CLASSES_ROOT\Interface\{82718C32-93CD-4ECC-BD6F-0F5AF70C4E89} "(Default)"
Type: REG_SZ
Data: IAcroQTPProxy
HKEY_CLASSES_ROOT\Interface\{82718C32-93CD-4ECC-BD6F-0F5AF70C4E89}\
ProxyStubClsid "(Default)"
Type: REG_SZ
Data: {00020424-0000-0000-C000-000000000046}
HKEY_CLASSES_ROOT\Interface\{82718C32-93CD-4ECC-BD6F-0F5AF70C4E89}\
ProxyStubClsid32 "(Default)"
Type: REG_SZ
```

```
Data: {00020424-0000-0000-C000-000000000046}
HKEY_CLASSES_ROOT\Interface\{82718C32-93CD-4ECC-BD6F-0F5AF70C4E89}\TypeLib
"(Default)"
Type: REG_SZ
Data: {2AABF103-0E9C-4F15-9F4E-3D344DFB9A30}
HKEY_CLASSES_ROOT\Interface\{82718C32-93CD-4ECC-BD6F-0F5AF70C4E89}\TypeLib
"Version"
Type: REG_SZ
Data: 1.0
HKEY_CLASSES_ROOT\Interface\{840E5481-71F5-4EC3-9C55-B916300405FE} "(Default)"
Type: REG_SZ
Data: IAcroQTPPlugin
HKEY_CLASSES_ROOT\Interface\{840E5481-71F5-4EC3-9C55-B916300405FE}\
ProxyStubClsid "(Default)"
Type: REG_SZ
Data: {00020424-0000-0000-C000-000000000046}
HKEY_CLASSES_ROOT\Interface\{840E5481-71F5-4EC3-9C55-B916300405FE}\
ProxyStubClsid32 "(Default)"
Type: REG_SZ
Data: {00020424-0000-0000-C000-000000000046}
HKEY_CLASSES_ROOT\Interface\{840E5481-71F5-4EC3-9C55-B916300405FE}\TypeLib
"(Default)"
Type: REG_SZ
Data: {C0FB90F3-F516-48B9-979A-4E60C7E69BF2}
HKEY_CLASSES_ROOT\Interface\{840E5481-71F5-4EC3-9C55-B916300405FE}\TypeLib
"Version"
Type: REG_SZ
Data: 1.0
HKEY_CLASSES_ROOT\TypeLib\{2AABF103-0E9C-4F15-9F4E-3D344DFB9A30}\1.0
"(Default)"
Type: REG_SZ
Data: AcroQTP Proxy 1.0 Type Library
HKEY_CLASSES_ROOT\TypeLib\{2AABF103-0E9C-4F15-9F4E-3D344DFB9A30}\1.0\0\win32
"(Default)"
Type: REG_SZ
Data: C:\Program Files\Adobe\Reader 10.0\Reader\plug_ins\Test_Tools\AcroQTP.
exe
HKEY_CLASSES_ROOT\TypeLib\{2AABF103-0E9C-4F15-9F4E-3D344DFB9A30}\1.0\FLAGS
"(Default)"
Type: REG_SZ
Data: 0
HKEY_CLASSES_ROOT\TypeLib\{2AABF103-0E9C-4F15-9F4E-3D344DFB9A30}\1.0\HELPPDIR
"(Default)"
Type: REG_SZ
Data: C:\Program Files\Adobe\Reader 10.0\Reader\plug_ins\Test_Tools
HKEY_CLASSES_ROOT\TypeLib\{C0FB90F3-F516-48B9-979A-4E60C7E69BF2}\1.0
"(Default)"
Type: REG_SZ
Data: AcroQTPPlugin Interface 1.0 Type Library
HKEY_CLASSES_ROOT\TypeLib\{C0FB90F3-F516-48B9-979A-4E60C7E69BF2}\1.0\0\win32
"(Default)"
Type: REG_SZ
Data: C:\Program Files\Adobe\Reader 10.0\Reader\plug_ins\Test_Tools\AcroQTP.
exe\2
HKEY_CLASSES_ROOT\TypeLib\{C0FB90F3-F516-48B9-979A-4E60C7E69BF2}\1.0\FLAGS
"(Default)"
Type: REG_SZ
Data: 0
HKEY_CLASSES_ROOT\TypeLib\{C0FB90F3-F516-48B9-979A-4E60C7E69BF2}\1.0\HELPPDIR
"(Default)"
```

```
Type: REG_SZ
Data: C:\Program Files\Adobe\Reader 10.0\Reader\plug_ins\Test_Tools
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Packages\TEAPackage\EnvDisplayName "AcroQTP"
Type: REG_SZ
Data: AcroQTP
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Packages\TEAPackage\ProgIDs "AcroQTP"
Type: REG_SZ
Data: AcroQTP.Proxy
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Packages\TEAPackage\Settings\AcroQTP "SnapshotMode"
Type: REG_DWORD
Data: 03, 00, 00, 00
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP "display name"
Type: REG_SZ
Data: AcroQTP
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "DefaultComplete"
Type: REG_DWORD
Data: 00, 00, 00, 00
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "DefaultMinimal"
Type: REG_DWORD
Data: 02, 00, 00, 00
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "DefaultNone"
Type: REG_DWORD
Data: 03, 00, 00, 00
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "DefaultPartial"
Type: REG_DWORD
Data: 01, 00, 00, 00
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "display name"
Type: REG_SZ
Data: Capture level
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "help string"
Type: REG_SZ
Data: Specifies which properties are captured for each object in a AcroQTP
application when it is captured for the Active Screen.
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "Internal Value"
Type: REG_SZ
Data: 3
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "type"
Type: REG_SZ
Data: selection 0\tComplete\n3\tPartial\n1\tMinimum\n2\tNone
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Snapshot\CaptureSettings\ZAcroQTP\SnapshotMode "Value path"
Type: REG_SZ
Data: Packages\TEAPackage\Settings\AcroQTP
Values changed: 10
HKEY_CURRENT_USER\Software\Mercury Interactive\QuickTest Professional\MicTest\
Packages\TEAPackage "display name"
Old type: REG_SZ
New type: REG_SZ
```



```
Old data:
New data: AcroQTP;
HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Explorer\
UserAssist\{CEBFF5CD-ACE2-4F4F-9178-9926F41749EA}\Count "HRZR_PGYFRFFVBA"
Old type: REG_BINARY
New type: REG_BINARY
Old data: (data too large: 1612 bytes)
New data: (data too large: 1612 bytes)
HKEY_CURRENT_USER\Software\Microsoft\Windows\CurrentVersion\Explorer\
UserAssist\{CEBFF5CD-ACE2-4F4F-9178-9926F41749EA}\Count "Zvpebfbsg.
NhgbTrarengrq.{P43N08S1-PQN4-QSS0-5536-ON91704Q600S}"
Old type: REG_BINARY
New type: REG_BINARY
Old data: 00, 00, 00, 00, 02, 00, 00, 00, 04, 00, 00, 00, FE, 7A, 00, 00, 00,
00, 80, BF, 00, 00, 80, BF, 00, 00, 80, BF, 00, 00, 80, BF, 00, 00, 80, BF,
00, 00, 80, BF, 00, 00, 80, BF, 00, 00, 80, BF, 00, 00, 80, BF, 00, 00, 80,
BF, FF, FF, FF, FF, 10, 07, CE, 39, 70, 7F, CC, 01, 00, 00, 00, 00
New data: 00, 00, 00, 00, 02, 00, 00, 00, 05, 00, 00, 00, 52, 0B, 02, 00, 00,
00, 80, BF, 00, 00, 80, BF, 00, 00, 80, BF, 00, 00, 80, BF, 00, 00, 80, BF,
00, 00, 80, BF, 00, 00, 80, BF, 00, 00, 80, BF, 00, 00, 80, BF, 00, 00, 80,
BF, FF, FF, FF, FF, 10, 07, CE, 39, 70, 7F, CC, 01, 00, 00, 00, 00
HKEY_CLASSES_ROOT\CLSID\{31345649-0000-0010-8000-00AA00389B71}\Pins\Input\
Types\{73646976-0000-0010-8000-00AA00389B71}\
{31345649-0000-0010-8000-00AA00389B71} "(Default)"
Old type: REG_NONE
New type: REG_NONE
Old data: (data too large: 260 bytes)
New data: (data too large: 260 bytes)
HKEY_CLASSES_ROOT\CLSID\{A2551F60-705F-11CF-A424-00AA003735BE}\Pins\Input\
Types\{73646976-0000-0010-8000-00AA00389B71}\
{00000000-0000-0000-0000-000000000000} "(Default)"
Old type: REG_NONE
New type: REG_NONE
Old data: (data too large: 260 bytes)
New data: (data too large: 260 bytes)
HKEY_LOCAL_MACHINE\SOFTWARE\Mercury Interactive\QuickTest Professional\
MicTest\Packages\TEAPackage "display name"
Old type: REG_SZ
New type: REG_SZ
Old data:
New data: AcroQTP;
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\
ShellCompatibility\Applications\InCtrl5.exe "FILEOPENBOGUSCTRLID"
Old type: REG_NONE
New type: REG_NONE
Old data: (data too large: 260 bytes)
New data: (data too large: 260 bytes)
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\
ShellCompatibility\Applications\InCtrl5.exe "FILEOPENBOGUSCTRLID"
Old type: REG_NONE
New type: REG_NONE
Old data: (data too large: 260 bytes)
New data: (data too large: 260 bytes)
HKEY_LOCAL_MACHINE\SOFTWARE\Microsoft\Windows\CurrentVersion\
ShellCompatibility\Applications\InCtrl5.exe "FILEOPENBOGUSCTRLID"
Old type: REG_NONE
New type: REG_NONE
Old data: (data too large: 260 bytes)
New data: (data too large: 260 bytes)
```



```
HKEY_LOCAL_MACHINE\Software\Microsoft\Windows\CurrentVersion\  
ShellCompatibility\Applications\InCtrl5.exe "FILEOPENBOGUSCTRLID"  
Old type: REG_NONE  
New type: REG_NONE  
Old data: (data too large: 260 bytes)  
New data: (data too large: 260 bytes)
```

## 2

## Guidelines for Creating Tests

Testing methodologies will vary slightly with the nature of the form being tested and testing environment. For example, prior to testing, the developer should know the following:

- Is LiveCycle ES or ADEP part of the workflow? Testing may require Flex components and a special test URL.
- What is the nature of forms in the workflow? There are several considerations:
  - Forms created with LiveCycle Designer ES are XML based and can have dynamic elements.
  - Forms created with Acrobat (Acroforms) are PDF language based.
  - Is the form “reader enabled” and given usage rights so that Adobe Reader users can perform actions that would otherwise be prohibited.
- Will forms be exercised in a standalone PDF viewer (Adobe Reader or Acrobat), or will they be exercised while viewed within a browser shell?

### 2.1 Guidelines for successful tests

The following guidelines will help you successfully record and playback tests:

- Run tests on the machine on which they were recorded.
- Record and run tests with only one Adobe client running.
- Record tests with only one PDF file open.

### 2.2 Supported form elements

The form elements supported by this release include those in [Table 4](#). Note the following:

- Forms created with LiveCycle Designer ES are XML based and can have dynamic elements.
- Forms created with Acrobat (Acroforms) are PDF language based.

**Tip:** LiveCycle/ADEP forms are XML based. forms. Thus, forms created by LiveCycle Designer are often referred to as XML forms. XFA is the name of the XML LiveCycle user.

**Table 4 Supported form elements**

Element	Acroform	XML (XFA)	Description
PDF Document	Yes	Yes	PDF Document
AcroField	N/A	N/A	Not visible within QTP
Button	Yes	Yes	Button

**Table 4 Supported form elements**

Element	Acroform	XML (XFA)	Description
CheckBox	Yes	Yes	Check Box
ComboBox	Yes		Combo Box
ListBox	Yes	Yes	List Box
RadioButton	Yes	Yes	Radio Button
RadioButtonList	Yes	Yes	Radio Button group
Signature	Yes	Yes	Signature field
Text	Yes	Yes	Text field
XFAForm	N/A	Yes	XFA Form
Table	N/A	Yes	Table
TableHeader	N/A	Yes	Table Header
TableRow	N/A	Yes	Table Row

## 2.3 Creating a new test script

### 2.3.1 Server testing

When Flex-based UI is part of the tested workflow, verify you have the requisite Flex components installed as described in [Chapter 1, "Installation and Configuration"](#).

Note that for testing, record and run properties must occur against a test URL for which the automation bits are turned on in the server's automation SWFs. These bits are on by default. When you start recording, set this URL. For example, if the server's main URL is:


```
http://<server name>:<server port>/<installation path>/Main.html
```

Then the URL to use for testing would be:

```
http://<server name>:<server port>/<installation path>/Main-auto.html
```

**Tip:** Additional information pertinent to testing within the LiveCycle/ADEP environment can be found at [http://livedocs.adobe.com/flex/3/html/agents\\_1.html](http://livedocs.adobe.com/flex/3/html/agents_1.html).


**Figure 7 QTP configuration: Pointing to the server automation URL**



## 2.3.2 Acrobat and Adobe Reader testing

There are no special steps required, however, if you would like QTP to invoke the standalone application as part of the test (as opposed to having the document already open), configure the record and run settings so that QTP can open the application.


**Figure 8 QTP configuration: Invoking the standalone PDF viewer**



## 2.3.3 Browser viewer testing

There are no special steps required, however, if you would like QTP to open a PDF in the browser, (as opposed to having the document already open), configure the record and run settings so that QTP can use an URL to find the file.

**Figure 9 QTP configuration: Invoking the standalone PDF viewer**



## 2.4 Testing events

Capturing events and other operations are an essential part of forms testing. [Table 5](#) lists the supported operations.

**Note:** In QTP, the operations appear in the Operations column. APTT's supported operations appear in addition to the standard events provided by QTP.

**Table 5 Operations provided and supported by the PDF Test Toolkit**

Operation	Description
Click	Generate a mouse click on the center of the field.
Select	Select the form field.
SetValue	Set the value of the field to specified value.
Typetext	Generate keystroke events for the field.
ClearEvents	Clear the event history.
EnableEvents	Enable capturing the event history.

**Table 5 Operations provided and supported by the PDF Test Toolkit**


Operation	Description
GetEvent	Set the property 'Event' to value of the specified event. Events are identified by index starting with 0 to 'NumEvents' - 1.
TestEvents	Test the event log to see if it contains the specified string and sets two values: <ul style="list-style-type: none"> <li>• <b>TestEventsPassed</b>: A boolean value indicating the success of the test.</li> <li>• <b>Event</b>: The value of the matching property.</li> </ul>
SetTimeOut	A PDFDoc method used to set the 'TimeOut' property to the specified value.

To add an event test on a form field such as a button or text field, perform the following:

1. Perform a form field action such as a button click.
2. Enable the events on the field you want to test:
  1. Select the row that contains the form field for which you want to add an action. In this example, it is a button.
  2. Right click and copy that row (including the action item, operation, value and documentation).
3. Paste the clipboard to the same row 4 TIMES. QTP will paste the new rows right above the old row. Now configure the three new rows:
  1. In the first row's operation column, select the operation cell and choose **Enable Events** from the drop down list. In the value column, select **True**.
  2. In the second row's operation column, select the operation cell and choose **Clear Events** from the drop down list. This clears the events so no previous events remain in the event stream.
  3. In the third row's operation column, select the operation cell and choose **Click** from the drop down list.
  4. In the fourth row's operation column, select the operation cell and choose **TestEvents** from the drop down list.
  5. For TestEvents add a value to the event name followed by space followed by full somExpression for the field you are adding the event to. For example, "click: xfa[0].form[0].form1[0].#subform[0].Button1[0]".

**Tip:** Make sure the event name is all lower case and there is a space next to the colon.

**Figure 10 Event testing: Selecting the event**



4. Add a check point to make sure the event has occurred.

**Tip:** The PDF test file needs to be open before setting a checkpoint.

1. Select the row containing the TestEvents operation.
2. Choose **Insert > Checkpoint > Standard Checkpoint**.
3. From the list of property values displayed uncheck all except testEventsPassed.
4. Set the value 1.
5. Stop recording.
6. Run the test.
7. Review the results:
  1. In the Test Results window on the left hand side, select the **TestClickIteration**.
  2. Right click and choose **Expand all**.
  3. Look for a green check mark or a red X mark indicating a pass or fail respectively.
  4. For each red X, select that action and double click.
  5. Compare the provided value with the test result value.

## 2.5 Checkpoint properties

The following tables list the supported checkpoint properties.

Any XML dynamic form or Acroform props not explicitly listed can still be used via QTP. To do so, enter the property manually along with the desired value. For more information, see the following:

- **Acroforms:** [http://www.adobe.com/devnet/acrobat/pdfs/js\\_api\\_reference.pdf](http://www.adobe.com/devnet/acrobat/pdfs/js_api_reference.pdf)
- **XML forms:** [http://help.adobe.com/en\\_US/lifecycle/8.2/lcdesigner\\_scripting\\_reference.pdf](http://help.adobe.com/en_US/lifecycle/8.2/lcdesigner_scripting_reference.pdf)
- **XFA specification:** [http://partners.adobe.com/public/developer/xml/index\\_arch.html#xfa\\_28](http://partners.adobe.com/public/developer/xml/index_arch.html#xfa_28)

**Table 6 Generic properties not subject to user customization**

Property	Description
afpModel	AcroQTP object model: not subject to user customization.
afpType	AcroQTP object type: not subject to user customization.
afpld	AcroQTP object ID: not subject to user customization.
ready	A PDFDoc property indicating the application is ready to perform the next operation: not subject to user customization.

**Note:** The following tables provide only a partial listing of available properties.

**Table 7 Acroform field properties**

Property	Description
hidden	Acrobat field identifier
name	The name of the form element
numFields	Acrobat document number of AcroForm fields
noontimes	Acrobat field number of list items
page	Acrobat field page number
rent	Acrobat field rectangle
read-only	Acrobat field access
type	Acrobat field type
userName	Acrobat field name
value As String	Acrobat field string value

Table 8 lists properties APTT provides to test various aspects of XFA objects.

**Table 8 PDF Test Toolkit properties**

Property	Description
timeout	Maximum milliseconds to wait for run command to complete.
event	The event resulting from a GetEvent or TestEvents operation.
events Enabled	A boolean value indicating the event logging state.



**Table 8 PDF Test Toolkit properties**

Property	Description
numEvents	Number of events in the event log - the maximum size of the log is 32 entries.
testEventsPassed	A boolean value indicating the success of the last TestEvents operation.

**Table 9 XML form field and QTP properties**

Property	Description
timeout	Maximum milliseconds to wait for run command to complete.
event	The event resulting from a GetEvent or TestEvents operation.
eventsEnabled	A boolean value indicating the event logging state.
numEvents	Number of events in the event log - the maximum size of the log is 32 entries.
testEventsPassed	A boolean value indicating the success of the last TestEvents operation.
access	field access
borderColor	field border color
borderWidth	field border width
highlight	field highlight
presence	field visibility
revalue	field raw value
rotate	field rotation
size	field size
somExpression	field identifier
x	field x position
y	field y position
h	field height
w	field width
Value	The field value. This value is an interpreted field value to simplify test generation. This value may be passed to the SetValue operation to set the field to the appropriate value.

## 2.6 Learning objects in the object repository

1. Open the PDF file containing the objects to add to the repository.
2. Choose the Add Objects icon (the icon with + sign) or the menu **Object > Add Objects to Local**.
3. QTP minimizes so that you can choose the form or the form field.
4. To learn only one object, click on the requisite form field; otherwise, click anywhere outside of a field.
5. Choose **Define Object Filter**, and make the appropriate selection.

6. Choose **OK**.

The form fields are now added to the repository.

## 2.7 Miscellaneous FAQs and operational details

### **Does APTT work with QTP version 10 and 11?**

Yes. In fact, much testing has been done with version 10 and 11

Using 10 has a benefit in that it does not record AVPageView statement for every click within a forms opened in Reader.

### **While recording in Adobe Reader, QTP 9.5 records an AVPageView statement for every click**

The issue does not appear in QTP 10. Delete the AVPageView statements before running your tests. Users who do not record tests but rather manually draft them will not encounter this minor issue.

### **Toggling between forms**

While recording a test that toggles between two forms, user has to first click on the title bar of the form for which he/she needs to record the actions. Otherwise the tool is not aware that the focus has shifted to a new form for which it has to record the actions.

### **An Acrobat recorded test fails when run on Adobe Reader**

A test recorded on one client may or may not run successfully in another client. It is best to record tests for a particular client.

### **How do I identify specific actions associated with fields?**

QTP truncates tree element names, so to figure out which field corresponds to which actions, go the checkpoint properties and look at the `afpid` value. Total name length is limited to 30 characters.

### **Why does QTP sometimes disappear during recording?**

QTP minimizes and the icon disappears from the task bar while in a record session when the user inserts a check point or output value or uses the Object Repository feature to learn the objects. QTP has not crashed; it is still open and recording.

### **Can recorded tests be run on other machines?**

Moving a client's position on the screen during recording does not impair a test; however, when a test is run on another machine, the test and recording is likely to fail because QTP might not be able to track the client. Differences in screen resolution may also have a negative impact.

### **Can a test be recorded at different points in time?**

No. One must Launch QTP first and then launch the PDF. Opening the PDF first results in launching AcroQTP.exe in Task Manager which doesn't work. Ideally, QTP should launch AcroQTP.exe.

To ensure a clean and operational test, record your test from beginning to end in a single session.

### **Can more than one client or PDF be open during recording?**

Recording is most reliable when occurring on one machine, with only one client running (Acrobat or Adobe Reader), and only one PDF open. QTP may record incorrectly if the testing environment contains too many variables.

### **Can I record digitally signing documents?**

Yes. However, you must already have a digital ID and a valid certificate available. QTP is not able to record all the steps or creating a digital ID on the fly.

### **I cannot PRINT when QTP is running. Why?**

PRINT is disabled when QTP is running and Reader Protected Mode is turned ON.

## **2.8 Errors**

### **Failed to find object: Failed to find Acrobat**

An unsupported version of Acrobat is being used or both Acrobat and Reader are installed.

**See the release notes for additional information.**

Experienced QTP users probably don't need help on setting up their environment or running the examples. However, if your first exposure to QTP is the result of using the Adobe PDF Test Toolkit, do the following:

- Install the toolkit in some convenient location.
- Create a directory where you'll deposit the results of your example tests.
- Follow all the steps described in [Chapter 1, "Installation and Configuration"](#).

The current release includes the following examples in <Toolkit installation directory>\test\_files\:

- [XML form in a browser](#)
- [Accessing unexposed properties](#)


### 3.1 XML form in a browser

This simple test requires no special configuration. To run it:

1. Open QTP.
2. Choose **File > Open > Test**.
3. Browse to <Toolkit installation directory>\test\_files\XMLForm\_in\_Browser.
4. Highlight XMLForm\_in\_Browser.
5. Choose **Open**.
6. Choose **Run**.

The test should run successfully with no failures.

Figure 11 Example QTP test: XML form in browser



## 3.2 Accessing unexposed properties

**Note:** The example files for this test reside in <Toolkit installation directory>\test\_files\CheckingUnexposedPropVals.

Not every property is exposed in the QTP's check point's standard properties dialog. Some properties are several layers down in a hierarchy and must be manually configured. The following example shows how to test for the border color of a TextField.

1. Copy the step containing an operation; for example, a "select" of the TextField1 for which you are checking the property border color twice.
2. Edit the first copy of this step: Highlight the Select operation of this step, and change it to GetROProperty from the drop down menu.
3. In the value column, enter the SOM to the property you are testing; in this case it will be xfa.form.form1.TextField1.border.edge.color.value.
4. Edit the second copy of the step you copied in step 1 above: Highlight the Select Operation and change it to CheckProperty from the drop down menu.
5. In the Value column, enter the SOM expression xfa.form.form1.TextField1.border.edge.color.value.
6. In the next sub column of the Value column of the step, enter 0,0,0 .

When you run the test, you will now be able to test the border color of the edge of TextField which is actually buried down in the hierarchy of the TextField1.

# Index

## A

- access 25
- Acrobat and Adobe Reader testing 20
- AcroField 18
- Acroform field properties 24
- afpld 24
- afpModel 24
- afpType 24

## B

- borderColor 25
- borderWidth 25
- Browser 5
- Browser viewer testing 21
- Button 18

## C

- CheckBox 19
- Checkpoint properties 24
- ClearEvents 21
- Click 21
- Client software 4
- ComboBox 19
- Creating a new test script 19

## E

- EnableEvents 21
- Event 22
- event 24, 25
- Event testing
  - Selecting the event 23
- Events provided and supported by the PDF Test Toolkit 21
- eventsEnabled 24, 25
- Example QTP test
  - XML form in browser 29
- Example QTP Tests 28

## F

- Flex Builder 3.0 6
- Flex Builder 3.0.2 update 6
- Flex plugin directory 7
- Flex QTP plugin installer 7

## G

- Generic properties not subject to user customization 24
- GetEvent 22
- Guidelines for Creating Tests 18

## H

- h 25

- Hardware 5
- highlight 25

## I

- Information only
  - Registry changes 11
- Install components to support Flex testing 6
- Install Flex Builder 6
- Install Quick Test Professional 8
- Install the Adobe PDF Test Toolkit 5
- Install the Flex plug-in for Quick Test Pro 6
- Install the PDF viewing client 5
- Installation 5
- Installation and Configuration 4

## L

- Learning objects in the object repository 25
- ListBox 19
- LiveCycle testing 19

## M

- Miscellaneous FAQs and operational details 26

## N

- numEvents 25

## O

- Operating system 5

## P

- PDF Document 18
- presence 25

## Q

- QTP
  - Add-In Manager 10
  - Additional installation components 9
  - Custom installation 9
  - Missing Flex components warning 7
- QTP configuration
  - Invoking the standalone PDF viewer 20, 21
  - Pointing to the LiveCycle automation URL 20

## R

- RadioButton 19
- RadioButtonList 19
- rawValue 25
- Registry entries 11
- rotate 25

## S

- Select 21
- Server software 4
- SetTimeout 22
- SetValue 21
- Signature 19
- size 25
- somExpression 25
- Supported form elements 18
- System requirements 4

## T

- Table 19
- TableHeader 19
- TableRow 19
- Test URLs 8
- TestEvents 22
- TestEventsPassed 22
- testEventsPassed 25
- Testing events 21
- Text 19
- timeout 24, 25
- Toggling between forms 26

- Typetext 21

## U

- Uninstalling the Adobe PDF Test Toolkit 11

## V

- Value 25
- Verify the server (LiveCycle ES) software 8

## W

- w 25
- What is the Adobe PDF Test Toolkit? 4

## X

- x 25
- XFAForm 19
- XML field properties 24, 25
- XML form in a browser 28

## Y

- y 25